

MOD. 802

Hydraulic double press for transfer printing and laminating
油压双工位热压机 · 用於热转印和层压



MODEL 802

Double flat bed press used for (双平板压机功能):

- Transfer printing (转移印花)
- Thermosetting - heatsetting (热固性-热定型)
- Film/web thermobonding (电影/网络热粘合)
- Plastification and coating with film (塑化和涂层与薄膜)
- Metallization and gold lamination (金属化和层压金)
- Transfer of special effects (es.: snake skin) 特效转移 (ES: 蛇皮)



1. Characteristics of printing planes (印刷机特点):

- 1.1 Planes number (台板数目): 2
- 1.2 Dimensions (尺寸): 1500 mm毫米 (59,06") x 1.000 mm毫米 (39,37")
- 1.3 Working dimensions (工作尺寸): perimeter limit 30 mm (1,18") - 50 mm (1,97") per side
每边周边限制30毫米 (1,18") - 50毫米 (1,97")

2. Heating and temperature control (加热和温度控制):

- 2.1. The printing plane is heated by electrical resistors (热压板以电动电阻加热)
- 2.2. The temperature of the printing plane is adjustable up to 230° C and controlled by electronic thermostat.
(热压板温度可调高达230度, 使用电子恒温器控制温度)

3. Other devices into machine (其它机器设备):

- 3.1. Motorized semi-automatic functions (电动半自动功能)
- 3.2. Automatic and recordable stroke times (自动记录行程时间)
- 3.3. Hydraulic pressure (液压)

4. Technical data (技术资料):

- 4.1. Installed power (安装功率): 10.5 kw/h
- 4.2. Average electrical consumption (平均耗电量): 7 kw/h
- 4.3. Overall dimensions (外形尺寸): width (宽) 1.970 mm毫米 (77,50"), Length(长) 2.400 mm毫米 (94,50"). Height(高) 1.250 mm毫米 (49,50").
- 4.4. Net weight (净重): 890 kg 公斤
- 4.5. Machine produced according to CE rules (机器按照CE规定生产)

All data and technical features are purely indicative and subjected to changes without prior notice

所有的数据和技术特征都是纯粹指示性的, 如有更改, 恕不另行通知

